

Claims

Sub 91
[c1]

A seat, comprising:

a first member, having a first forward portion and a first rearward portion;
 at least one connection member, in communication with said first member;
 a second member, having a second forward portion and a second rearward portion, in communication with said at least one connection member;
 wherein said at least one connection member disposes said first forward portion a desired distance from said second forward portion; and
 wherein said at least one connection member disposes said first rearward portion a second desired distance from said second rearward portion.

B1 Cont
Sub 92
[c2]

The seat of claim 1, wherein said first member and said second member are asymmetrical halves of the seat.

[c3]

The seat of claim 1, wherein said first member and said second member are contoured to receive a user's buttocks.

B1 Cont
[c4]

The seat of claim 2, wherein said first member and said second member are contoured to receive a user's buttocks.

[c5]

The seat of claim 1, wherein said at least one connection member is at least one turnbuckle.

[c6]

The seat of claim 1, wherein said at least one connection member is mounted on a single seat bar.

[c7]

The seat of claim 1, wherein said at least one connection member is at least one rod in combination with at least one bolt.

Sub 93
[c8]

A seat, comprising:

a first member, having a first forward portion and a first rearward portion;
 a seat rail disposed below said first member;
 a second member, having a second forward portion and a second rearward portion, in communication with said seat rail;
 wherein said seat rail disposes said first forward portion a desired distance from said second forward portion; and

wherein said seat rail disposes said first rearward portion a second desired distance from said second rearward portion.

B1/cont
[c9] The seat of claim 8, further comprising a seat rail disposed below said first member and said second member.

[c10] The seat of claim 8, wherein said seat rail is generally "U" shaped, such that the bottom of the "U" shape is under said first rearward portion and said second rearward portion.

B1/cont
[c11] The seat of claim 9, wherein said seat rail is bifurcated, such that a first portion of said seat rail is disposed under said first member, and a second portion of said seat rail is disposed under said second member.

[c12] The seat of claim 11, wherein said first portion of said seat rail is joined to said second portion of said seat rail via at least one turnbuckle in combination with at least two screws.

[c13] The seat of claim 1, wherein said first member and said second member, when brought close together by said at least one connection member, do not interlock, but have an airflow space in between them.

[c14] The seat of claim 8, wherein said first member and said second member, when brought close together by said seat rail, do not interlock, but have an airflow space in between them.

[c15] The seat of claim 1, wherein said first rearward portion is wider than said first forward portion.

[c16] The seat of claim 1, wherein said second rearward portion is wider than said second forward portion.

[c17] The seat of claim 8, wherein said first rearward portion is wider than said first forward portion.

[c18] The seat of claim 8, wherein said second rearward portion is wider than said second forward portion.

- [c19] ~~The seat of claim 1, wherein said first member is disposed in a different horizontal plane than said second member.~~
- [c20] ~~The seat of claim 8, wherein said first member is disposed in a different horizontal plane than said second member.~~